

# UCP700+ Technical Data Sheet

Advanced Biofilm Protection for Maximum Performance



## UCP700+ Innovation, The First Biofilm - Resistant Pump



Up to six 3.6m cabinets

## UCP700+ Specifications

### In the box

- 500mm Flexi Drain Connector
- High Grade SW Tank Connector
- Test Dye
- Hose Clip

### Key Features

- Ag+ Ultra Antibacterial Shield: Prevents biofilm formation for 5-8 years
- Biocidal Mesh Filtration: Added biocidal action to prevent biofilm growth
- Superior grade components and construction
- AI improved functionality, Integral NRV, High level alarm

UCP700+ SPECIFICATIONS	
Mains supply	230V-50Hz - 123W - 1.0A
Max flow rate	700 l/h
Max discharge head	23m
Water levels	On=50mm, Off=37mm, Alarm=54mm
Alarm contact	NO 8A resistive - 250V
Thermal protection	None
Pump dimensions	L 605 x W 200 x H 76mm
Weight (inc box)	± 5Kg
Packaging	Unitary

ACCESSORIES	
Description	Products
Dairy Pump Drain Connector (CPH17)	
Condensate Drain Support Twin Pk (APC19)	
Gel-clear 'Helix' Condensate Hose (H20CH1/2)	

Gel-clear Ltd 145 Bolton Road, Darwen, Lancashire, England BB3 1DF

Get in touch: ☎ 01254 760002 | ✉ info@gel-clear.co.uk | 🌐 www.gel-clear.co.uk